

DATASHEET

Front-door station

carus ARGOS		
Functionality calling, speaking, hearing		
number of call destinations		telephone book for up to 100 persons
voice transmission		hands-free talking
acoustic parameter		adjustable
echo suppression		full duplex high performance echo suppression
audio coding		G.711 (A/μ-Law) G.729
Functionality seeing		
display		color touchscreen LCD
size resolution		14.5 cm (5.7") with 640 x 480 pixel
brightness of the display		controlled by ambient light manually adjustable
camera		CMOS: 2 megapixel with color sensor
opening angle (fish eye lens)	°	100
frame rate		up to 30 images per second
video compression		H.264 MJPEG JPEG
video resolution		QSVGA in SIP video, QVGA CIF VGA SVGA in stream
electronic PTZ		yes
anti flicker function		yes
front glass		hardened AR coated
Access control		
identification		RFID code combined
storage		identification storage for up to 1000 persons
codelock		individual code, 3 to 8 digits
RFID reader		MIFARE® (adaptable for MIFARE® DESFire®, LEGIC® and iCLASS®)
Mechanical features		
type of installation		flush-mount
type of housing		flush-mount box (included in the delivery)
material of the housing		aluminium with structured surface refined by hand
color of the housing		silver black
weight	kg	2.9
Electrical features		
power supply		Power-over-Ethernet (PoE) 802.3af and 802.3at
power supply, alternatively		12 V 0,5 A or via 2-wire interface
max. input current I(Pmax)	mA	10
System features		
protocols		SIP RFC 3261, compatible to SIP (image) telephones or softphones TCP/UDP/IP RTP HTTP DNS NTP DHCP SNMP
Peer-to-Peer-Betrieb		possible
registry server		intergrated (max. 16 clients)
interfaces		ethernet 10/100 BaseT to RJ45 socket
trigger input		2 x (door release button feedback contact)
relay changeover contact		2 x (door opener light)
2-wire interface		to spring terminal (with optional 2-wire kit)
system protection		tamper switch acceleration sensor
Commissioning and maintenance		
configuration		via LCD menu web browser

IPvideofront-doorstation ARGOS
for flush-mount
CAE3000-IP-0150



IPvideofront-doorstation ARGOS
in aluminium anodised black
CAE3000-IP-0156



For questions regarding
planning, please contact
our technical support .

Send your inquiry
by mail to:
hotline@tcsag.de


Subject to technical changes.
Images shown are not binding.

DATASHEET

Front-door station

Carus

Dimensions in H x W (x D)		
housing	mm	345 x 192 x 8 (52 incl. flush-mount box)
installation	mm	350 x 192 x 8 (52 incl. flush-mount box)
Climatic characteristics		
acceptable ambient temperature	°C	-20 to +60
degree of protection		IP65
Scope of delivery		
front-door station		CAE3000-IP-015x(incl.productinformation,assemblyinstruction)



For questions regarding planning, please contact our technical support.

Send your inquiry by mail to:
hotline@tcsag.de

Subject to technical changes.
Images shown are not binding.