## Series Carus ADAPTO CAI2200 | CAI2210

Functionality calling, speaking, hearing		
voice transmission		hands-free talking   simplex communication (can be activated)
acoustic parameter (adjustable factory setting)		ring tone volume
number of ring tones		13
number of acoustic ring tone distinctions		3 (up to 2 from front-door stations)
internal call (can be activated)		at function key   comfort keypad
parallel call (can be activated)		at function key   comfort keypad
call diversion (can be activated)		at function key   comfort keypad
automatic hands-free talking after internal call		yes (can be activated)
audio privacy function and automatic call cut-off		yes
Functionality video		
size of the display	cm	8.9
type of display		digital TFT
resolution	pixel	420 x 240
Functionality switching, controlling, displaying		
door release function		at door release button
floor door release function		at door release button (can be activated)
light switch function		at light switch button
control function		at function key (adjustable factory setting)
alternating control function (ON   OFF)		yes
max. number of additional functions for calling and switching (with status indication)		10 (at comfort keypad)
door release automatic		at function key (can be activated)
image activation   camera selection		at image button
camera control		via navigation buttons (4)
ring tone volume		continuously adjustable
color saturation   brightness		continuously adjustable
optical indication ring tone mute		LED (red)
optical indication call diversion resp. door release automatic		LED (red)
optical indication door and internal calls (short-term memory)		LED (green)
optical indication door standby time and on-service call		LED (green)
optical indication of a busy line		LED (green)
status indication		sensor with binary input
Electrical features		
input current I(a)	mA	0.5
input current I(P), standby	mA	7.5
input current I(Pmax), max.	mA	167
additional connections		floor door push button
Mechanical features		
type of installation		surface mount   desktop accessory
type of housing		surface-mounted housing
material of the housing		aluminium anodised
surface		structured surface finish refined by hand
color of the housing		silver   champagne   bronze   black
material of the buttons		aluminium anodised
button labelling		lasered
labelling field		extractable



Video indoor station with comfort keypad in aluminium anodised silver CAE2200-0150



Indoor station with comfort keypad in aluminium anodised champagne CAE2200-0152



Video indoor station with comfort keypad in aluminium anodised bronze CAE2200-0151



Video indoor station with comfort keypad in aluminium anodised black CAE2200-0156



For questions regarding planning, please contact our technical support .

Send your inquiry by mail to: hotline@tcsag.de

Subject to technical changes. Images shown are not binding.

## DATASHEET

Indoor station

	polarity-free and short-circuit protected 2-wire TCS:BUS
	6
	possible
	ring tone volume   ring tone selection   color saturation   brightness
	ring tone selection   internal call   parallel call   call diversion   door release automatic   light switch function   control function(s)
	simplex communication   ring tone selection   internal call   parallel call   call diversion   door release automatic   control function(s)
mm	163 x 284 x 16 CAI2200)   156 x 284 x 150 (CAI2210)
mm	180 x 284 x 19 (CAI2100)
mm	1.600
°C	0 to +40
	unlimited
	CAI2200-015x (extraction tool, installation screws)
	CAI2210-015x (incl. 2.5 m cable with RS45 connector)
	mm



Video indoor station with comfort keypad as desktop device with continuously adjustable inclination CAE2210-0150



For questions regarding planning, please contact our technical support .

Send your inquiry by mail to: hotline@tcsag.de

Subject to technical changes. Images shown are not binding.