

Series Carus ADAPTO CAI2100 | CAI2110

Functionality calling, speaking, hearing

voice transmission		hands-free talking simplex communication (can be activated)
acoustic parameter (adjustable factory setting)		ring tone volume
number of ring tones		13
number of acoustic ring tone distinctions		3 (up to 2 from front-door stations)
internal call (can be activated)		at function key
parallel call (can be activated)		at function key
call diversion (can be activated)		at function key
automatic hands-free talking after internal call		yes (can be activated)
audio privacy function and automatic call cut-off		yes

Functionality video

size of the display	cm	8.9
type of display		digital TFT
resolution	pixel	420 x 240

Functionality switching, controlling, displaying

door release function		at door release button
floor door release function		at door release button (can be activated)
light switch function		at light switch button
control function		at function key (adjustable factory setting)
door release automatic		at function key (can be activated)
image activation camera selection		at image button
camera control		via navigation buttons (4)
ring tone volume		continuously adjustable
color saturation brightness		continuously adjustable
optical indication ring tone mute		LED (red)
optical indication call diversion resp. door release automatic		LED (red)
optical indication door and internal calls (short-term memory)		LED (green)
optical indication door standby time and on-service call		LED (green)
optical indication of a busy line		LED (green)

Electrical features

input current I(a)	mA	0.5
input current I(P), standby	mA	5
input current I(Pmax), max.	mA	155
additional connections		floor door push button

Mechanical features

type of installation		surface mount desktop accessory
type of housing		surface-mounted housing
material of the housing		aluminium anodised
surface		structured surface finish refined by hand
color of the housing		silver champagne bronze black
material of the buttons		aluminium anodised
button labelling		lasered

System features

signal transmission and power supply		polarity-free and short-circuit protected 2-wire TCS:BUS
wiring technique (number of wires)		6
mixed installation of audio, video, access control in one system		possible

Video indoor station for hands-free talking in aluminium anodised silver
CAE2100-0150



Indoor station for hands-free talking in aluminium anodised champagne
CAE2100-0152



Video indoor station for hands-free talking in aluminium anodised bronze
CAE2100-0151



Video indoor station for hands-free talking in aluminium anodised black
CAE2100-0156



For questions regarding planning, please contact our technical support .

Send your inquiry by mail to:
hotline@tcsag.de

Subject to technical changes.
Images shown are not binding.

DATASHEET

Indoor station

Carus

Commissioning and maintenance		
manually adjustable parameter		ring tone volume ring tone selection color saturation brightness
parameter that can be adjusted with Service Device		ring tone selection internal call parallel call call diversion door release automatic light switch function control function(s)
parameter that can be adjusted with software configo™		simplex communication ring tone selection internal call parallel call call diversion door release automatic control function(s)
Dimensions in H x W (x D)		
housing	mm	163 x 192 x 16 (CAI2100) 156 x 192 x 150 (CAI2110)
space for mounting and operating the device	mm	180 x 192 x 19 (CAI2100)
recommended mounting height (for display)	mm	1.600
Climatic characteristics		
acceptable ambient temperature	°C	0 to +40
UV resistance		unlimited
Scope of delivery		
indoor station Carus ADAPTO		CAI2100-015x (extraction tool, installation screws)
indoor station Carus ADAPTO as desktop accessory		CAI2110-015x (incl. 2.5 m cable with RS45 connector)

Video indoor station as desktop device with continuously adjustable inclination

CAE2110-0150



For questions regarding planning, please contact our technical support .

Send your inquiry by mail to:
hotline@tcsag.de

Subject to technical changes.
Images shown are not binding.